

# Commercial Steam Boilers

**PENNCO**   
**SILVER**  
CAST IRON BOILERS

**41K** Series  
Gas-Fired Steam Modular Boiler



## Electronic Ignition Base Standard Equipment:

- Base
- Fire Door
- Burner Orifice
- Manifold
- Main and Pilot Burner
- Electronic Pilot Gas Valve
- Intermittent Pilot Module
- Complete Jacket Assembly

## Steam Trim Package:

- Low Water Cut-Off
- Glass Gauge Set
- Safety Valve
- Steam Gauge
- Pressure Limit
- Drain Valve

41K Series Boiler Bases are pre-assembled at the factory with burner manifold, burner orifices, gas valves and electronic ignition installed, ready for field installation of the pre-tested sections and appropriate packages.

## Plug 'N Play Harness and Junction Box

Individual base and junction box controls are designed for easy installation with Plug 'n Play harnesses. The entire boiler links together in a "snap". A color-coded factory supplied harness eliminates wiring errors



**Pennco SILVER makes Simple Comfort, Affordable.**


[www.pennco boilers.com](http://www.pennco boilers.com)  
PN 240009465 [11/05/20]

# 41K Series

## Gas-Fired Steam Modular Boiler



www.pennco boilers.com



### RIGHT & LEFT END TAPPINGS

A: Supply & Return	4"
B: Primary LWCO & Gauge Glass Set	1/2"
C: Drain (Left & Right End)	3/4"
D: Plugged	1/2"
E: Accessories	1"
*F: Safety Valve	1"
G: Plugged or Electronic (Probe Type) LWCO	3/4"

## Specifications:

MODEL	AHRI CERTIFIED RATINGS						DIMENSIONS					
	Input MBH <sup>(1)</sup>	Gross Output MBH <sup>(1)</sup>	Steam PPF <sup>(2)</sup>	Steam Sq. Ft. <sup>(3)</sup>	Steam MBH <sup>(2)</sup>	Thermal Efficiency	Base Size & Flue Outlet			Chimney Size <sup>(4)</sup> I.D. x Ht.	Flue Collector Size to Chimney	Horsepower Gross Output <sup>(5)</sup>
							300 8"	400 10"	500 12"			
41K300S	300	233	1.333	729	175	77%	1	0	0	8" x 20'	8	6.96
41K400S	400	310	1.333	971	233	77%	0	1	0	10" x 20'	10	9.25
41K500S	500	388	1.333	1213	291	77%	0	0	1	12" x 20'	12	11.58
41K600S	600	465	1.333	1454	349	77%	2	0	0	12" x 20'	12	13.88
41K700S	700	543	1.333	1696	407	77%	1	1	0	12" x 20'	12	16.21
41K800S	800	620	1.333	1938	465	77%	0	2	0	14" x 20'	14	18.51
41K900S	900	698	1.333	2183	524	77%	0	1	1	14" x 20'	14	20.84
41K1000S	1000	775	1.333	2421	581	77%	0	0	2	14" x 20'	14	23.13
41K1100S	1100	853	1.333	2667	640	77%	1	2	0	16" x 20'	16	25.46
41K1200S	1200	930	1.333	2908	698	77%	0	3	0	16" x 20'	16	27.76
41K1300S	1300	1008	1.333	3150	756	77%	1	0	2	16" x 20'	16	30.09
41K1400S	1400	1085	1.333	3392	814	77%	0	1	2	18" x 20'	18	32.39
41K1500S	1500	1163	1.333	3633	872	77%	0	0	3	18" x 20'	18	34.72

1. Ratings are at sea level to 2,000 feet. For altitudes above 2,000 feet, reduce all ratings 4% for each 1,000 feet above sea level.
2. Net steam ratings based on piping and pickup allowance of 1.333 (300-1500). Contact Technical Support before selecting boiler for installations having unusual piping and pick-up factors, such as intermittent system operations, extensive piping systems, etc.
3. Ratings in square feet are computed at 240 Btuh/square foot for steam boilers.
4. Chimney sizes shown are one option based on a typical venting system as shown in Figure 6 of the Installation Manual, and sized according to the National Fuel Gas Code, assuming Type B double wall vent and vent connectors, other venting system designs are acceptable as shown on Flue Connection and Venting section of the installation manual. For further chimney design and sizing information, consult the National Fuel Gas Code, ANSI Z223.1/NFPA 54-latest revision, or ASHRAE HVAC Systems and Equipment Handbook, Chimney, Gas Vent, and Fireplace Systems, or the Standard for Chimneys, Fireplaces, Vents, and Solid Fuel Burning Appliances. NFPA 211. Follow standard engineering practice.
5. Ratings based on 33,500 Btuh per horsepower.



ECR International, Inc. 2201 Dwyer Avenue, Utica, NY 13501  
Tel. 800 253 7900  
www.ecrinternational.com



All specifications subject to change without notice.  
©2020 ECR International, Inc.  
PN 240009465 Rev. [11/05/20]